

# Spack - a package manager for HPC systems

Moritz Siegel



# Why Package Manager?

Many installations of the **same** software but with different:

- ▶ Hardware
- ▶ Versions
- ▶ Compilers
- ▶ Flags
- ▶ Dependencies

Example MPI:

18 providers x 30 versions x 6 compilers x 22 flags x 31 dependencies =  
= **2209680 variants** on VSC-5 alone!



We have 3 different **spack trees** for different architecture:

Cluster	CPU	GPU	Spack Tree
VSC-4	Intel	NO	<b>skylake</b>
VSC-5	AMD	NO	<b>zen</b>
VSC-5	AMD	YES	<b>cuda-zen</b>

All packages **only** work on their architecture!



The current spack tree is shown on the left of the command line **prompt**:

```
1 skylake trainee00@144:~$  
2 zen trainee00@155:~$  
3 cuda-zen trainee00@155:~$
```

On login the **spack tree** for the current architecture is set.



All spack commands work on the **current tree**.

Type **sky**, **zen** or **cuz** to **switch** to a spack tree:

```
1 skylake trainee00@l44:~$ zen
2 zen trainee00@l44:~$ cuz
3 cuda-zen trainee00@l44:~$ sky
4 skylake trainee00@l44:~$
```

You are on the **same node 144** the whole time.



Find your package, like **openmpi**:

```
1 zen trainee00@l44:~$ spack find openmpi
```

Use "@" to show specific **version** only:

```
2 skylake trainee00@l44:~$ spack find openmpi@4.1.4
```

```
3 zen trainee00@l55:~$ spack find openmpi@3
```

All **python** packages have a leading "py-" like in **py-numpy**.

All **R** packages start with "r-" like in **r-brew**.



Add `-l` to show the unique package **hash** too:

```
1 skylake trainee00@l44:~$ spack find -l openmpi@4.1.4
```

Use **any** spack command with this hash, and a "/" in front:

```
2 skylake trainee00@l44:~$ spack find -l /2vqdnay
```



Use `spack search` to search for a **hash** of an old VSC installation:

```
1 zen trainee00@l155:~$ spack search /asdc2mk
```

You get some similar modules on the **current** spack tree.





Use "%" to only show packages **compiled** with intel, gcc, aocc, etc:

```
1 skylake trainee00@l144:~$ spack find openmpi %intel
2 zen trainee00@l155:~$ spack find openmpi %aocc
3 cuda-zen trainee00@l155:~$ spack find openmpi %gcc
```

Combine "%" and "@" to show specific **compiler version** only:

```
4 zen trainee00@l155:~$ spack find openmpi %gcc@9
```



Use `spack find -v` to see the **flags** of a package:

```
1 skylake trainee00@l44:~$ spack find -v openmpi@4.1.4
```

Use "+" or "~" to show only packages that **have/not have** that flag:

```
2 cuda-zen trainee00@l55:~$ spack find openmpi +cuda
```



Use `spack find -d` to show the **dependencies** of a package:

```
1 skylake trainee00@l44:~$ spack find -d /xt53foa
```

Use "`^`" to only show packages **A** that depend on **B**:

```
2 skylake trainee00@l44:~$ spack find -d py-numpy ^intel-oneapi-mkl
```

```
3 zen trainee00@l55:~$ spack find -d py-numpy ^openblas
```



Use `spack load` to load your package:

```
1 skylake trainee00@l44:~$ spack load openmpi@4.1.4
```

Add the unique **hash** to load that **exact** package:

```
2 skylake trainee00@l44:~$ spack load py-numpy/ygplffi  
3 zen trainee00@l55:~$ spack load py-numpy/dzcpm7y  
4 cuda-zen trainee00@l55:~$ spack load py-numpy/bctcmkr
```

All these packages are **numpy**, but built for different architectures.



Type `spack find --loaded` to list loaded packages:

```
1 skylake trainee00@l44:~$ spack find --loaded
2 -- linux-almalinux8-zen3 / gcc@12.2.0 -----
3 o6ui7qb berkeley-db@18.1.40          4o2lz14 libbsd@0.11.5
4 qta2z6t openssl@1.1.1s              sultos7 py-setuptools@63.0.0
5 ...
```

Type `spack unload` to unload all packages.



Every package installed with spack creates a module file:

```
1 <package>/<version>-<compiler>-<version>-<hash>  
2 openmpi/3.1.6-aocc-4.0.0-k4glowk  
3 openmpi/4.1.4-gcc-12.2.0-je3hmfk  
4 openmpi/4.1.4-intel-2021.7.1-lex74to
```

The **hash** at the end, like **k4glowk** is the same as in spack.



- login to VSC-4/5.
- switch between the three spack trees **zen**, **skylake** and **cuda-zen**.
- find a **hdf5** variant compiled with **aocc** at **zen**.
- find a **openmpi** with **cuda** support at **cuda-zen**.
- find a **numpy** including **intel-oneapi-mkl** at **skylake**.
- load any **openmpi** package, then list all the loaded packages.
- find out what old package once was **/asdc2mk**.

